

# Package ‘fauxpas’

February 20, 2026

**Title** HTTP Error Helpers

**Description** HTTP error helpers. Methods included for general purpose HTTP error handling, as well as individual methods for every HTTP status code, both via status code numbers as well as their descriptive names. Supports ability to adjust behavior to stop, message or warning. Includes ability to use custom whisker template to have any configuration of status code, short description, and verbose message. Currently supports integration with 'crul', 'curl', and 'httr'.

**Version** 0.6.0

**License** MIT + file LICENSE

**URL** <https://sckott.github.io/fauxpas/>,  
<https://github.com/sckott/fauxpas>

**BugReports** <https://github.com/sckott/fauxpas/issues>

**VignetteBuilder** knitr

**Encoding** UTF-8

**Language** en-US

**Imports** R6 (>= 2.1.2), httpcode (>= 0.3.0), whisker

**Suggests** crul (>= 0.5.0), curl (>= 2.2), httr (>= 1.2.0), testthat,  
knitr, rmarkdown

**RoxygenNote** 7.3.3

**X-schema.org-applicationCategory** Web

**X-schema.org-keywords** http, https, API, web-services, curl, errors,  
error

**NeedsCompilation** no

**Author** Scott Chamberlain [aut, cre] (ORCID:  
<<https://orcid.org/0000-0003-1444-9135>>)

**Maintainer** Scott Chamberlain <[myrmecocystus@gmail.com](mailto:myrmecocystus@gmail.com)>

**Repository** CRAN

**Date/Publication** 2026-02-20 06:40:10 UTC

## Contents

Error . . . . .	2
Error-Classes . . . . .	3
find_error_class . . . . .	4
http100 . . . . .	5
<b>Index</b>	<b>10</b>

---

Error	<i>Error class</i>
-------	--------------------

---

### Description

Error class

### Arguments

behavior	Behavior of the error. default: auto. See Details
message_template	A message template. optional. use whisker templating. names to use are: reason and status. use in template like <code>{{reason}}</code> and <code>{{status}}</code> . Note that <code>{{message}}</code> that is used in <code>message_template_verbose</code> will be ignored here.
call.	(logical) indicating if the call should become part of the error message. Default: FALSE
message_template_verbose	A verbose message template. optional. use whisker templating. names to use are: reason, status, message. use in template like <code>{{reason}}</code> , <code>{{status}}</code> , and <code>{{message}}</code> . Note that this is ignored here, but is used in the HTTP* methods (e.g. HTTPBadRequest)
muffle	(logical) whether to not respond when status codes in 1xx-3xx series. Default: FALSE

### behavior parameter options

- stop - use stop
- warning - use warning
- message - use message
- auto - toggle between stop and message depending on the HTTP status code series. Defaults will be:
  - 1xx: message
  - 2xx: message
  - 3xx: message
  - 4xx: stop
  - 5xx: stop

Of course, you can always override the defaults.

**Methods**

- `do(response, mssg, template)`:  
Execute condition, whether it be message, warning, or error.
  - `response`: is any response from **crul**, **curl**, or **httr** Execute condition, whether it be message, warning, error, or your own custom function. This method uses `message_template_verbose`, and uses it's default value.
  - `mssg`: character string message to include in call. ignored if template does not have a message entry
  - `template`: set a template; by default uses `message_template`
- `set_behavior(behavior)`:
  - Set behavior, same as setting behavior on initializing with `$new()`

**See Also**

[http](#), [Error-Classes](#)

**Examples**

```
Error$new()
# reset behavior
(z <- Error$new())
z$set_behavior("warning")
z
```

---

Error-Classes

*Individual error classes*

---

**Description**

These error classes are for each HTTP error, and inherit from the [Error](#) class in this package.

**Details**

In addition to what's available in [Error](#), these classes have a single variable `mssg` that is the very verbose complete message describing the HTTP condition in detail. You can include that message in your condition by using `do_verbose` (see below)

**Methods**

In addition to the methods documented in [Error](#), these classes also have:

- `do_verbose(response, template)`:  
Execute condition, whether it be message, warning, or error.
  - `response`: is any response from `crul`, `curl`, or `httr` Execute condition, whether it be message, warning, error, or your own custom function. This method uses `message_template_verbose`, and uses it's default value.
  - `template`: a template to use for the verbose message, see [Error](#) for details

**See Also**[Error, http](#)**Examples**

```

HTTPRequestURITooLong$new(
  message_template = "{{reason}} ..... {{status}}",
  message_template_verbose = "{{reason}} .>.>.>.> {{status}}\n {{message}}"
)

```

---

find_error_class	<i>Find error classes</i>
------------------	---------------------------

---

**Description**

Find error classes

**Usage**

```
find_error_class(status_code)
```

**Arguments**

status\_code (numeric,integer) A status code

**Value**

an object of class R6ClassGenerator. call \$new() to initialize a new instance

**See Also**[Error, Error-Classes](#)**Examples**

```

find_error_class(414)
find_error_class(418)
find_error_class(505)

# initialize the class
find_error_class(418)$new()

# not found
## Not run: find_error_class(999)

```

---

http100 *higher level error wrappers*

---

**Description**

higher level error wrappers

**Usage**

http100(response, behavior = "auto", message\_template, muffle = FALSE)

http101(response, behavior = "auto", message\_template, muffle = FALSE)

http102(response, behavior = "auto", message\_template, muffle = FALSE)

http200(response, behavior = "auto", message\_template, muffle = FALSE)

http201(response, behavior = "auto", message\_template, muffle = FALSE)

http202(response, behavior = "auto", message\_template, muffle = FALSE)

http203(response, behavior = "auto", message\_template, muffle = FALSE)

http204(response, behavior = "auto", message\_template, muffle = FALSE)

http205(response, behavior = "auto", message\_template, muffle = FALSE)

http206(response, behavior = "auto", message\_template, muffle = FALSE)

http207(response, behavior = "auto", message\_template, muffle = FALSE)

http208(response, behavior = "auto", message\_template, muffle = FALSE)

http226(response, behavior = "auto", message\_template, muffle = FALSE)

http300(response, behavior = "auto", message\_template, muffle = FALSE)

http301(response, behavior = "auto", message\_template, muffle = FALSE)

http302(response, behavior = "auto", message\_template, muffle = FALSE)

http303(response, behavior = "auto", message\_template, muffle = FALSE)

http304(response, behavior = "auto", message\_template, muffle = FALSE)

http305(response, behavior = "auto", message\_template, muffle = FALSE)

http306(response, behavior = "auto", message\_template, muffle = FALSE)  
http307(response, behavior = "auto", message\_template, muffle = FALSE)  
http308(response, behavior = "auto", message\_template, muffle = FALSE)  
http400(response, behavior = "auto", message\_template, muffle = FALSE)  
http401(response, behavior = "auto", message\_template, muffle = FALSE)  
http402(response, behavior = "auto", message\_template, muffle = FALSE)  
http403(response, behavior = "auto", message\_template, muffle = FALSE)  
http404(response, behavior = "auto", message\_template, muffle = FALSE)  
http405(response, behavior = "auto", message\_template, muffle = FALSE)  
http406(response, behavior = "auto", message\_template, muffle = FALSE)  
http407(response, behavior = "auto", message\_template, muffle = FALSE)  
http408(response, behavior = "auto", message\_template, muffle = FALSE)  
http409(response, behavior = "auto", message\_template, muffle = FALSE)  
http410(response, behavior = "auto", message\_template, muffle = FALSE)  
http411(response, behavior = "auto", message\_template, muffle = FALSE)  
http412(response, behavior = "auto", message\_template, muffle = FALSE)  
http413(response, behavior = "auto", message\_template, muffle = FALSE)  
http414(response, behavior = "auto", message\_template, muffle = FALSE)  
http415(response, behavior = "auto", message\_template, muffle = FALSE)  
http416(response, behavior = "auto", message\_template, muffle = FALSE)  
http417(response, behavior = "auto", message\_template, muffle = FALSE)  
http418(response, behavior = "auto", message\_template, muffle = FALSE)  
http419(response, behavior = "auto", message\_template, muffle = FALSE)  
http420(response, behavior = "auto", message\_template, muffle = FALSE)

http421(response, behavior = "auto", message\_template, muffle = FALSE)  
http422(response, behavior = "auto", message\_template, muffle = FALSE)  
http423(response, behavior = "auto", message\_template, muffle = FALSE)  
http424(response, behavior = "auto", message\_template, muffle = FALSE)  
http425(response, behavior = "auto", message\_template, muffle = FALSE)  
http426(response, behavior = "auto", message\_template, muffle = FALSE)  
http428(response, behavior = "auto", message\_template, muffle = FALSE)  
http429(response, behavior = "auto", message\_template, muffle = FALSE)  
http431(response, behavior = "auto", message\_template, muffle = FALSE)  
http440(response, behavior = "auto", message\_template, muffle = FALSE)  
http444(response, behavior = "auto", message\_template, muffle = FALSE)  
http449(response, behavior = "auto", message\_template, muffle = FALSE)  
http450(response, behavior = "auto", message\_template, muffle = FALSE)  
http451(response, behavior = "auto", message\_template, muffle = FALSE)  
http494(response, behavior = "auto", message\_template, muffle = FALSE)  
http495(response, behavior = "auto", message\_template, muffle = FALSE)  
http496(response, behavior = "auto", message\_template, muffle = FALSE)  
http497(response, behavior = "auto", message\_template, muffle = FALSE)  
http498(response, behavior = "auto", message\_template, muffle = FALSE)  
http499(response, behavior = "auto", message\_template, muffle = FALSE)  
http500(response, behavior = "auto", message\_template, muffle = FALSE)  
http501(response, behavior = "auto", message\_template, muffle = FALSE)  
http502(response, behavior = "auto", message\_template, muffle = FALSE)  
http503(response, behavior = "auto", message\_template, muffle = FALSE)

```

http504(response, behavior = "auto", message_template, muffle = FALSE)
http505(response, behavior = "auto", message_template, muffle = FALSE)
http506(response, behavior = "auto", message_template, muffle = FALSE)
http507(response, behavior = "auto", message_template, muffle = FALSE)
http508(response, behavior = "auto", message_template, muffle = FALSE)
http509(response, behavior = "auto", message_template, muffle = FALSE)
http510(response, behavior = "auto", message_template, muffle = FALSE)
http511(response, behavior = "auto", message_template, muffle = FALSE)
http598(response, behavior = "auto", message_template, muffle = FALSE)
http599(response, behavior = "auto", message_template, muffle = FALSE)
http520(response, behavior = "auto", message_template, muffle = FALSE)
http521(response, behavior = "auto", message_template, muffle = FALSE)
http522(response, behavior = "auto", message_template, muffle = FALSE)
http523(response, behavior = "auto", message_template, muffle = FALSE)
http524(response, behavior = "auto", message_template, muffle = FALSE)
http525(response, behavior = "auto", message_template, muffle = FALSE)
http526(response, behavior = "auto", message_template, muffle = FALSE)
http527(response, behavior = "auto", message_template, muffle = FALSE)
http(response, behavior = "auto", message_template, muffle = FALSE)

```

### Arguments

response	The result of a call via <b>crul</b> , <b>curl</b> , or <b>httr</b>
behavior	Behavior of the error. default: auto. See Details
message_template	A message template. optional. use whisker templating. names to use are: reason and status. use in template like <code>{{reason}}</code> and <code>{{status}}</code> . Note that <code>{{message}}</code> that is used in <code>message_template_verbos</code> will be ignored here.
muffle	(logical) whether to not respond when status codes in 1xx-3xx series. Default: FALSE

**behavior parameter options**

- stop - use stop
- warning - use warning
- message - use message
- auto - toggle between stop and message depending on the HTTP status code series. Defaults will be:
  - 1xx: message
  - 2xx: message
  - 3xx: message
  - 4xx: stop
  - 5xx: stop

Of course, you can always override the defaults.

**using package curl**

curl responses are simple lists, so we have little to go on to make sure it's a response from the **curl** package. We check for list names internally but of course you could pass in a list with the right named elements, while the values are complete nonsense, in which case we'll probably fail badly. There's not much we can do.

**Note**

These http\* methods only use \$do and not \$do\_verbose.

**See Also**

[Error, Error-Classes](#)

**Examples**

```
res <- list(url="https://a.com", status_code=200, type="application/xml",
  headers=charToRaw("a"), modified=NA, times=5, content=charToRaw('b'))
http(res, behavior = "message")
```

# Index

Error, [2](#), [3](#), [4](#), [9](#)

Error-Classes, [3](#), [3](#), [4](#), [9](#)

find\_error\_class, [4](#)

http, [3](#), [4](#)

http (http100), [5](#)

http100, [5](#)

http101 (http100), [5](#)

http102 (http100), [5](#)

http200 (http100), [5](#)

http201 (http100), [5](#)

http202 (http100), [5](#)

http203 (http100), [5](#)

http204 (http100), [5](#)

http205 (http100), [5](#)

http206 (http100), [5](#)

http207 (http100), [5](#)

http208 (http100), [5](#)

http226 (http100), [5](#)

http300 (http100), [5](#)

http301 (http100), [5](#)

http302 (http100), [5](#)

http303 (http100), [5](#)

http304 (http100), [5](#)

http305 (http100), [5](#)

http306 (http100), [5](#)

http307 (http100), [5](#)

http308 (http100), [5](#)

http400 (http100), [5](#)

http401 (http100), [5](#)

http402 (http100), [5](#)

http403 (http100), [5](#)

http404 (http100), [5](#)

http405 (http100), [5](#)

http406 (http100), [5](#)

http407 (http100), [5](#)

http408 (http100), [5](#)

http409 (http100), [5](#)

http410 (http100), [5](#)

http411 (http100), [5](#)

http412 (http100), [5](#)

http413 (http100), [5](#)

http414 (http100), [5](#)

http415 (http100), [5](#)

http416 (http100), [5](#)

http417 (http100), [5](#)

http418 (http100), [5](#)

http419 (http100), [5](#)

http420 (http100), [5](#)

http421 (http100), [5](#)

http422 (http100), [5](#)

http423 (http100), [5](#)

http424 (http100), [5](#)

http425 (http100), [5](#)

http426 (http100), [5](#)

http428 (http100), [5](#)

http429 (http100), [5](#)

http431 (http100), [5](#)

http440 (http100), [5](#)

http444 (http100), [5](#)

http449 (http100), [5](#)

http450 (http100), [5](#)

http451 (http100), [5](#)

http494 (http100), [5](#)

http495 (http100), [5](#)

http496 (http100), [5](#)

http497 (http100), [5](#)

http498 (http100), [5](#)

http499 (http100), [5](#)

http500 (http100), [5](#)

http501 (http100), [5](#)

http502 (http100), [5](#)

http503 (http100), [5](#)

http504 (http100), [5](#)

http505 (http100), [5](#)

http506 (http100), [5](#)

http507 (http100), [5](#)

http508 (http100), [5](#)

- http509 (http100), 5
- http510 (http100), 5
- http511 (http100), 5
- http520 (http100), 5
- http521 (http100), 5
- http522 (http100), 5
- http523 (http100), 5
- http524 (http100), 5
- http525 (http100), 5
- http526 (http100), 5
- http527 (http100), 5
- http598 (http100), 5
- http599 (http100), 5
- HTTPAccepted (Error-Classes), 3
- HTTPAlreadyReported (Error-Classes), 3
- HTTPATimeoutOccurred (Error-Classes), 3
- HTTPAuthenticationTimeout (Error-Classes), 3
- HTTPBadGateway (Error-Classes), 3
- HTTPBadRequest (Error-Classes), 3
- HTTPBandwidthLimitExceeded (Error-Classes), 3
- HTTPBlockedByWindowsParentalControls (Error-Classes), 3
- HTTPCertError (Error-Classes), 3
- HTTPClientClosedRequest (Error-Classes), 3
- HTTPConflict (Error-Classes), 3
- HTTPConnectionTimedOut (Error-Classes), 3
- HTTPContinue (Error-Classes), 3
- HTTPCreated (Error-Classes), 3
- HTTPExpectationFailed (Error-Classes), 3
- HTTPFailedDependency (Error-Classes), 3
- HTTPForbidden (Error-Classes), 3
- HTTPFound (Error-Classes), 3
- HTTPGatewayTimeout (Error-Classes), 3
- HTTPGone (Error-Classes), 3
- HTTPHTTPToHTTPS (Error-Classes), 3
- HTTPHTTPVersionNotSupported (Error-Classes), 3
- HTTPImUsed (Error-Classes), 3
- HTTPInsufficientStorage (Error-Classes), 3
- HTTPInternalServerError (Error-Classes), 3
- HTTPInvalidSSLCertificate (Error-Classes), 3
- HTTPLengthRequired (Error-Classes), 3
- HTTPLocked (Error-Classes), 3
- HTTPLoginTimeout (Error-Classes), 3
- HTTPLoopDetected (Error-Classes), 3
- HTTPMethodFailure (Error-Classes), 3
- HTTPMethodNotAllowed (Error-Classes), 3
- HTTPMisdirectedRequest (Error-Classes), 3
- HTTPMovedPermanently (Error-Classes), 3
- HTTPMultipleChoices (Error-Classes), 3
- HTTPMultiStatus (Error-Classes), 3
- HTTPNetworkAuthenticationRequired (Error-Classes), 3
- HTTPNetworkConnectTimeoutError (Error-Classes), 3
- HTTPNetworkReadTimeoutError (Error-Classes), 3
- HTTPNoCert (Error-Classes), 3
- HTTPNoContent (Error-Classes), 3
- HTTPNonAuthoritativeInformation (Error-Classes), 3
- HTTPNoResponse (Error-Classes), 3
- HTTPNotAcceptable (Error-Classes), 3
- HTTPNotExtended (Error-Classes), 3
- HTTPNotFound (Error-Classes), 3
- HTTPNotImplemented (Error-Classes), 3
- HTTPNotModified (Error-Classes), 3
- HTTPOK (Error-Classes), 3
- HTTPOriginIsUnreachable (Error-Classes), 3
- HTTPPartialContent (Error-Classes), 3
- HTTPPaymentRequired (Error-Classes), 3
- HTTPPermanentRedirect (Error-Classes), 3
- HTTPPreconditionFailed (Error-Classes), 3
- HTTPPreconditionRequired (Error-Classes), 3
- HTTPProcessing (Error-Classes), 3
- HTTPProxyAuthenticationRequired (Error-Classes), 3
- HTTPRailgunError (Error-Classes), 3
- HTTPRequestEntityTooLarge (Error-Classes), 3
- HTTPRequestHeaderFieldsTooLarge (Error-Classes), 3
- HTTPRequestHeaderTooLarge (Error-Classes), 3
- HTTPRequestRangeNotSatisfiable

- (Error-Classes), 3
- HTTPRequestTimeout (Error-Classes), 3
- HTTPRequestURITooLong (Error-Classes), 3
- HTTPResetContent (Error-Classes), 3
- HTTPRetryWith (Error-Classes), 3
- HTTPSeeOther (Error-Classes), 3
- HTTPServiceUnavailable (Error-Classes),  
3
- HTTPSSLHandshakeFailed (Error-Classes),  
3
- HTTPSwitchProtocol (Error-Classes), 3
- HTTPSwitchProxy (Error-Classes), 3
- HTTPTeaPot (Error-Classes), 3
- HTTPTemporaryRedirect (Error-Classes), 3
- HTTPTokenExpiredInvalid  
(Error-Classes), 3
- HTTPTooManyRequests (Error-Classes), 3
- HTTPUnauthorized (Error-Classes), 3
- HTTPUnavailableForLegalReasons  
(Error-Classes), 3
- HTTPUnorderedCollection  
(Error-Classes), 3
- HTTPUnprocessableEntity  
(Error-Classes), 3
- HTTPUnsupportedMediaType  
(Error-Classes), 3
- HTTPUpgradeRequired (Error-Classes), 3
- HTTPUseProxy (Error-Classes), 3
- HTTPVariantAlsoNegotiates  
(Error-Classes), 3
- HTTPWebServerIsDown (Error-Classes), 3
- HTTPWebServerReturnedUnknownError  
(Error-Classes), 3