

Package ‘gsynth’

March 27, 2026

Type Package

Title Generalized Synthetic Control Method

Version 1.4.0

Date 2026-03-27

Maintainer Yiqing Xu <yiqingxu@stanford.edu>

Author Yiqing Xu [aut, cre] (ORCID: <<https://orcid.org/0000-0003-2041-6671>>),

Licheng Liu [aut],

Ziyi Liu [aut],

Shiyun Hu [aut]

Description Conducts causal inference with interactive fixed-effect models. It imputes counterfactuals for each treated unit using control group information based on a linear interactive fixed effects model that incorporates unit-specific intercepts interacted with time-varying coefficients. This method generalizes the synthetic control method to the case of multiple treated units and variable treatment periods, and improves efficiency and interpretability. See Xu (2017) <[doi:10.1017/pan.2016.2](https://doi.org/10.1017/pan.2016.2)> for details.

URL <https://yiqingxu.org/packages/gsynth/>,

<https://github.com/xuyiqing/gsynth>

BugReports <https://github.com/xuyiqing/gsynth/issues>

NeedsCompilation no

Encoding UTF-8

License MIT + file LICENSE

Imports ggplot2 (>= 2.1.0), fect (>= 2.0.0), panelView (>= 1.1.17)

Suggests testthat (>= 3.0.0)

Depends R (>= 2.10)

LazyData true

Config/testthat/edition 3

RoxygenNote 7.3.2

Repository CRAN

Date/Publication 2026-03-27 20:40:02 UTC

Contents

| | |
|--------------|----|
| effect | 2 |
| gsynth | 3 |
| plot.gsynth | 7 |
| print.gsynth | 9 |
| simdata | 10 |
| turnout | 10 |

| | |
|--------------|-----------|
| Index | 11 |
|--------------|-----------|

| | |
|--------|--|
| effect | <i>Cumulative or Sub-group Treatment Effects</i> |
|--------|--|

Description

Calculates cumulative or sub-group treatment effects

Usage

```
effect(x, cumu = TRUE, period = NULL, id = NULL, plot = FALSE)
```

Arguments

| | |
|--------|---|
| x | a <code>gsynth</code> object. |
| cumu | a logical flag indicating whether to calculate cumulative effects or not. |
| id | a string vector specifying a sub-group of treated units that treatment effects are to be averaged on. |
| period | a two-element numeric vector specifying the range of term during which treatment effects are to be accumulated. If left blank, atts at all post-treatment periods will be calculated. |
| plot | a logical flag indicating whether to plot the cumulative effects. |

Value

| | |
|----------|---------------------------------|
| catt | esimated (cumulative) atts. |
| est.catt | uncertainty estimates for catt. |

Author(s)

Yiqing Xu <yiqingxu@stanfprd.edu>, Stanford University

References

Yiqing Xu. 2017. "Generalized Synthetic Control Method: Causal Inference with Interactive Fixed Effects Models." *Political Analysis*, Vol. 25, Iss. 1, January 2017, pp. 57-76.

See Also[gsynth](#)

gsynth*Generalized Synthetic Control Method*

Description

Implements the generalized synthetic control method based on interactive fixed effect models.

Usage

```
gsynth(formula=NULL, data, Y, D, X = NULL, na.rm = FALSE,
       index, weight = NULL, force = "unit", cl = NULL, r = 0,
       lambda = NULL, nlambda = 10, CV = TRUE, criterion = "mspe",
       k = 5, EM = FALSE, estimator = "gsynth",
       se = FALSE, nboots = 200,
       inference = NULL, parallel = TRUE,
       cores = NULL, tol = 0.001, seed = NULL, min.T0 = 5,
       alpha = 0.05, normalize = FALSE)
```

Arguments

| | |
|---------|--|
| formula | an object of class "formula": a symbolic description of the model to be fitted. |
| data | a data frame (must be with a dichotomous treatment but balanced is not required). |
| Y | outcome. |
| D | treatment. |
| X | time-varying covariates. |
| na.rm | a logical flag indicating whether to list-wise delete missing data. The algorithm will report an error if missing data exist. |
| index | a two-element string vector specifying the unit (group) and time indicators. Must be of length 2. |
| weight | a string specifying the weighting variable(if any) to estimate the weighted average treatment effect. Default is weight = NULL. |
| force | a string indicating whether unit or time fixed effects will be imposed. Must be one of the following, "none", "unit", "time", or "two-way". The default is "unit". |
| cl | a string indicator the cluster variable. The default value is NULL. If cl = NULL, bootstrap will be blocked at unit level (only for non-parametric bootstrap). |
| r | an integer specifying the number of factors. If CV = TRUE, the cross validation procedure will select the optimal number of factors from r to 5. |
| lambda | a single or sequence of positive numbers specifying the hyper-parameter sequence for matrix completion method. If lambda is a sequence and CV = 1, cross-validation will be performed. |

| | |
|-----------|--|
| nlambda | an integer specifying the length of hyper-parameter sequence for matrix completion method. Default is nlambda = 10. |
| CV | a logical flag indicating whether cross-validation will be performed to select the optimal number of factors or hyper-parameter in matrix completion algorithm. If r is not specified, the procedure will search through r = 0 to 5. |
| criterion | a string specifying the criteria used for determining the number of factors. Choose from c("mspe", "pc"). "mspe" stands for the mean squared prediction error obtained through the loocv procedure, and "pc" stands for a kind of information criterion. If criterion = "pc", the number of factors that minimize "pc" will be selected. Default is criterion = "mspe". |
| k | a positive integer specifying cross-validation times for matrix completion algorithm. Default is k = 5. |
| EM | a logical flag indicating whether an Expectation Maximization algorithm will be used (Gobillon and Magnac 2016). |
| estimator | a string that controls the estimation method: "gsynth" (generalized synthetic control, default), "ife" (interactive fixed effects with EM algorithm), or "mc" (matrix completion method). |
| se | a logical flag indicating whether uncertainty estimates will be produced. |
| nboots | an integer specifying the number of bootstrap runs. Ignored if se = FALSE. |
| inference | a string specifying which type of inferential method will be used, either "parametric" or "nonparametric". "parametric" is recommended when the number of treated units is small. parametric bootstrap is not valid for matrix completion method. Ignored if estimator = "mc". |
| parallel | a logical flag indicating whether parallel computing will be used in bootstrapping and/or cross-validation. Ignored if se = FALSE. |
| cores | an integer indicating the number of cores to be used in parallel computing. If not specified, the algorithm will use the maximum number of logical cores of your computer (warning: this could prevent you from multi-tasking on your computer). |
| tol | a positive number indicating the tolerance level. |
| seed | an integer that sets the seed in random number generation. Ignored if se = FALSE and r is specified. |
| min.T0 | an integer specifying the minimum value of pre-treatment periods. Treated units with pre-treatment periods less than that will be removed automatically. This item is important for unbalanced panels. If users want to perform cross validation procedure to select the optimal number of factors from (r.min, r.max), they should set min.T0 larger than (r.max+1) if no individual fixed effects or (r.max+2) otherwise. If there are too few pre-treatment periods among all treated units, a smaller value of r.max is recommended. |
| alpha | a positive number in the range of 0 and 1 specifying significant levels for uncertainty estimates. The default value is alpha = 0.05. |
| normalize | a logic flag indicating whether to scale outcome and covariates. Useful for accelerating computing speed when magnitude of data is large. The default is normalize=FALSE. |

Details

gsynth implements the generalized synthetic control method. It imputes counterfactuals for each treated unit using control group information based on a linear interactive fixed effects model that incorporates unit-specific intercepts interacted with time-varying coefficients. It generalizes the synthetic control method to the case of multiple treated units and variable treatment periods, and improves efficiency and interpretability. It allows the treatment to be correlated with unobserved unit and time heterogeneities under reasonable modeling assumptions. With a built-in cross-validation procedure, it avoids specification searches and thus is easy to implement. Data must be with a dichotomous treatment.

Value

| | |
|-------------|--|
| Y.dat | a matrix storing data of the outcome variable. |
| Y | name of the outcome variable. |
| D | name of the treatment variable. |
| X | name of the time-varying control variables. |
| index | name of the unit and time indicators. |
| id | a vector of unit IDs. |
| time | a vector of time periods. |
| obs.missing | a matrix storing status of each unit at each time point. 0 for missing, 1 for control group units, 2 for treat group units at pre-treatment period, 3 for treat group units at post-treatment period, and 4 for removed treated group units. Useful for unbalanced panel data. |
| id.tr | a vector of IDs for the treatment units. |
| id.co | a vector of IDs for the control units. |
| removed.id | a vector of IDs for units that are removed. |
| D.tr | a matrix of treatment indicator for the treated unit outcome. |
| I.tr | a matrix of observation indicator for the treated unit outcome. |
| Y.tr | data of the treated unit outcome. |
| Y.ct | predicted counterfactuals for the treated units. |
| Y.co | data of the control unit outcome. |
| eff | difference between actual outcome and predicted $Y(0)$. |
| Y.bar | average values of Y.tr, Y.ct, and Y.co over time. |
| att | average treatment effect on the treated over time (it is averaged based on the timing of the treatment if it is different for each unit). |
| att.avg | average treatment effect on the treated. |
| force | user specified force option. |
| sameT0 | TRUE if the timing of the treatment is the same. |
| T | the number of time periods. |
| N | the total number of units. |
| p | the number of time-varying observables. |

| | |
|--------------|--|
| Ntr | the number of treated units. |
| Nco | the number of control units. |
| T0 | a vector that stores the timing of the treatment for balanced panel data. |
| tr | a vector indicating treatment status for each unit. |
| pre | a matrix indicating the pre-treatment/non-treatment status. |
| post | a matrix indicating the post-treatment status. |
| r.cv | the number of factors included in the model – either supplied by users or automatically chosen via cross-validation. |
| lambda.cv | the optimal hyper-parameter in matrix completion method chosen via cross-validation. |
| res.co | residuals of the control group units. |
| beta | coefficients of time-varying observables from the interactive fixed effect model. |
| sigma2 | the mean squared error of interactive fixed effect model. |
| IC | the information criterion. |
| PC | the proposed criterion for determining factor numbers. |
| est.co | result of the interactive fixed effect model based on the control group data. |
| eff.cnt | difference between actual outcome and predicted $Y(0)$; rearranged based on the timing of the treatment. |
| Y.tr.cnt | data of the treated unit outcome, rearranged based on the timing of the treatment. |
| Y.ct.cnt | data of the predicted $Y(0)$, rearranged based on the timing of the treatment. |
| MSPE | mean squared prediction error of the cross-validated model. |
| CV.out | result of the cross-validation procedure. |
| niter | the number of iterations in the estimation of the interactive fixed effect model. |
| factor | estimated time-varying factors. |
| lambda.co | estimated loadings for the control group. |
| lambda.tr | estimated loadings for the treatment group. |
| wgt.implicit | estimated weights of each of the control group unit for each of the treatment group unit. |
| mu | estimated ground mean. |
| xi | estimated time fixed effects. |
| alpha.tr | estimated unit fixed effects for the treated units. |
| alpha.co | estimated unit fixed effects for the control units. |
| validX | a logic value indicating if multicollinearity exists. |
| inference | a string indicating bootstrap procedure. |
| est.att | inference for att. |
| est.att.avg | inference for att.avg. |
| est.beta | inference for beta. |
| est.ind | inference for att of each treated unit. |
| att.avg.boot | bootstrap results for att.avg. |
| att.boot | bootstrap results for att. |
| beta.boot | bootstrap results for beta. |

Author(s)

Yiqing Xu <yiqingxu@stanford.edu>, Stanford University

References

Laurent Gobillon and Thierry Magnac, 2016. "Regional Policy Evaluation: Interactive Fixed Effects and Synthetic Controls." *The Review of Economics and Statistics*, July 2016, Vol. 98, No. 3, pp. 535–551.

Yiqing Xu. 2017. "Generalized Synthetic Control Method: Causal Inference with Interactive Fixed Effects Models." *Political Analysis*, Vol. 25, Iss. 1, January 2017, pp. 57-76.

Athey S, Bayati M, Doudchenko N, et al. Matrix completion methods for causal panel data models[J]. arXiv preprint arXiv:1710.10251, 2017.

For more details, see <https://yiqingxu.org/packages/gsynth/>.

For more details about the matrix completion method, see <https://github.com/susanathey/MCPanel>.

See Also

[plot.gsynth](#) and [print.gsynth](#)

Examples

```
library(gsynth)
data(gsynth)
out <- gsynth(Y ~ D + X1 + X2, data = simdata, parallel = FALSE,
             index = c("id", "time"), force = "two-way",
             CV = TRUE, r = c(0, 5), se = FALSE)
print(out)
```

plot.gsynth

Plotting

Description

Visualizes estimation results of the generalized synthetic control method.

Usage

```
## S3 method for class 'gsynth'
plot(x, type = "gap", xlim = NULL, ylim = NULL,
     xlab = NULL, ylab = NULL, legendOff = FALSE, raw = "none",
     main = NULL, nfactors = NULL, id = NULL, axis.adjust = FALSE,
     theme.bw = TRUE, shade.post = FALSE, ...)
```

Arguments

| | |
|-------------|--|
| x | a <code>gsynth</code> object. |
| type | a string that specifies the type of the plot. Must be one of the following: "gap" (plotting the average treatment effect on the treated; "raw" (plotting the raw data); "counterfactual", or "ct" for short, (plotting predicted $Y(0)$'s); "factors" (plotting estimated factors); "loadings" (plotting the distribution of estimated factor loadings); "missing" (plotting status of each unit at each time point). |
| xlim | a two-element numeric vector specifying the range of x-axis. When class of time variable is string, must specify not original value but a counting number e.g. <code>xlim=c(1,30)</code> . |
| ylim | a two-element numeric vector specifying the range of y-axis. |
| xlab | a string indicating the label of the x-axis. |
| ylab | a string indicating the label of the y-axis. |
| legendOff | a logical flag controlling whether to show the legend. |
| raw | a string indicating whether or how raw data for the outcome variable will be shown in the "counterfactual" plot. Ignored if type is not "counterfactual". Must be one of the following: "none" (not showing the raw data); "band" (showing the middle 90 percentiles of the raw data); and "all" (showing the raw data as they are). |
| main | a string that controls the title of the plot. If not supplied, no title will be shown. |
| nfactors | a positive integer that specifies the number of factors to be shown. The maximum number is 4. Ignored if type is not "factors" |
| id | a unit identifier of which the predicted counterfactual or the difference between actual and predicted counterfactual is to be shown. It can also be a vector specifying units to be plotted if <code>type=="missing"</code> when data magnitude is large. Ignored if type is none of "missing", "counterfactual", "gap". |
| axis.adjust | a logical flag indicating whether to adjust labels on x-axis. Useful when class of time variable is string and data magnitude is large. |
| theme.bw | a logical flag indicating whether to use a black/white theme. |
| shade.post | a logical flag controlling whether to shade the post-treatment periods. |
| ... | other argv. |

Details

`plot.gsynth` visualizes the raw data used by, or estimation results obtained from, the generalized synthetic control method.

Author(s)

Yiqing Xu <yiqingxu@stanford.edu>, Stanford University

References

Yiqing Xu. 2017. "Generalized Synthetic Control Method: Causal Inference with Interactive Fixed Effects Models." *Political Analysis*, Vol. 25, Iss. 1, January 2017, pp. 57-76.

See <https://yiqingxu.org/packages/gsynth/> for more detailed information.

See Also

[gsynth](#) and [print.gsynth](#)

`print.gsynth`

Print Results

Description

Print results of the generalized synthetic control method.

Usage

```
## S3 method for class 'gsynth'  
print(x, ...)
```

Arguments

`x` a [gsynth](#) object.
`...` other argv.

Author(s)

Yiqing Xu <yiqingxu@stanfprd.edu>, Stanford University

References

Yiqing Xu. 2017. "Generalized Synthetic Control Method: Causal Inference with Interactive Fixed Effects Models." *Political Analysis*, Vol. 25, Iss. 1, January 2017, pp. 57-76.

For more details, see <https://yiqingxu.org/packages/gsynth/>.

See Also

[gsynth](#) and [plot.gsynth](#)

simdata

simdata

Description

A simulated dataset.

Format

dataframe

References

Yiqing Xu. 2017. "Generalized Synthetic Control Method: Causal Inference with Interactive Fixed Effects Models." *Political Analysis*, Vol. 25, Iss. 1, January 2017, pp. 57-76.

For more details, see <https://yiqingxu.org/packages/gsynth/>.

turnout

turnout

Description

State-level voter turnout data.

Format

dataframe

References

Melanie Jean Springer. 2014. *How the States Shaped the Nation: American Electoral Institutions and Voter Turnout, 1920-2000*. University of Chicago Press.

Yiqing Xu. 2017. "Generalized Synthetic Control Method: Causal Inference with Interactive Fixed Effects Models." *Political Analysis*, Vol. 25, Iss. 1, January 2017, pp. 57-76.

For more details, see <https://yiqingxu.org/packages/gsynth/>.

Index

* datasets

simdata, [10](#)

turnout, [10](#)

effect, [2](#)

gsynth, [2](#), [3](#), [3](#), [8](#), [9](#)

plot.gsynth, [7](#), [7](#), [9](#)

print.gsynth, [7](#), [9](#), [9](#)

simdata, [10](#)

turnout, [10](#)