

# PackageManager

**Easily download and install GAP  
packages**

1.6.1

5 February 2025

**Michael Young**

**Michael Young**

Email: [mct25@st-andrews.ac.uk](mailto:mct25@st-andrews.ac.uk)

Homepage: <https://myoung.uk/work>

Address: School of Computer Science  
University of St Andrews  
Jack Cole Building, North Haugh  
St Andrews, Fife, KY16 9SX  
United Kingdom

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	What does the <code>PackageManager</code> package do? . . . . .	3
1.2	What does the <code>PackageManager</code> package not do? . . . . .	3
1.3	A quick example . . . . .	3
<b>2</b>	<b>Commands</b>	<b>5</b>
2.1	Main commands . . . . .	5
2.2	Info warnings . . . . .	7
2.3	Manual compilation . . . . .	7
	<b>Index</b>	<b>9</b>

# Chapter 1

## Introduction

### 1.1 What does the **PackageManager** package do?

This package provides the ability to install or remove a package using a single command: `InstallPackage` (2.1.1) or `RemovePackage` (2.1.3). The user can specify a package to install using its name, or using a URL to an archive, a repository, or a `PackageInfo.g` file. When installing, **PackageManager** also attempts to compile the package, build its documentation if necessary, and ensure that its dependencies are also installed.

### 1.2 What does the **PackageManager** package not do?

At present, **PackageManager** is fairly basic, without many of the advanced features available in package managers such as `pip` or `apt`. For instance, the user cannot update all packages in one command. Removing a package will not remove any of its dependencies, since we do not track how packages were installed. When a package is installed, no tests are run to ensure that it is compatible with the installed version of GAP. Any of these features might be added in the future. Other feature requests can be posted on the issue tracker at <https://github.com/gap-packages/PackageManager/issues>.

### 1.3 A quick example

**PackageManager** is distributed with GAP, so it should already be available on your system. To load the package, call:

Example

```
gap> LoadPackage("PackageManager");
```

Note that you'll need to do this in each session when you want to use the package manager. To install the latest deposited version of the **Digraphs** package, use the following:

Example

```
gap> InstallPackage("digraphs");
```

To uninstall it later, use the following:

Example

```
gap> RemovePackage("digraphs");
```

PackageManager also supports version control repositories. To install the latest version of the `curlInterface` package from [GitHub](#), use the following:

Example

```
gap> InstallPackage("https://github.com/gap-packages/curlInterface.git");
```

## Chapter 2

# Commands

### 2.1 Main commands

#### 2.1.1 InstallPackage

▷ `InstallPackage(string[, version][, interactive])` (function)

**Returns:** true or false

Attempts to download and install a package. The argument *string* should be a string containing one of the following:

- the name of a package;
- the URL of a package archive, ending in `.tar.gz` or `.tar.bz2`;
- the URL of a git repository, ending in `.git`;
- the URL of a valid `PackageInfo.g` file.

The package will then be downloaded and installed, along with any additional packages that are required in order for it to be loaded. Its documentation will also be built if necessary. If this installation is successful, or if this package is already installed, `true` is returned; otherwise, `false` is returned.

By default, packages will be installed in the `pkg` subdirectory of `GAPInfo.UserGapRoot` (see **(Reference: GAP Root Directories)**). Note that this location is not the default user `pkg` location on Mac OSX, but it will be created on any system if not already present. Note also that starting GAP with the `-r` flag will cause all packages in this directory to be ignored.

Certain decisions, such as installing newer versions of packages, will be confirmed by the user via an interactive shell – to avoid this interactivity and use sane defaults instead, the optional argument *interactive* can be set to `false`.

To see more information about this process while it is ongoing, see `InfoPackageManager` (2.2.1).

If *string* is the name of the package in question then one can specify a required package version via a string as value of the optional argument *version*, which is interpreted as described in Section **(Reference: Version Numbers)**. In particular, if *version* starts with `=` then the function will try to install exactly the given version, and otherwise it will try to install a version that is not smaller than the given one. If an installed version satisfies the condition on the version then `true` is returned without an attempt to upgrade the package. If the package is not yet installed or if no installed version satisfies the version condition then an upgrade is tried only if the package version that is listed on the GAP webpages satisfies the condition. (The function will not update a dev version of the package

if a version number is prescribed; otherwise it could happen that one updates the installation and afterwards notices that the version condition is still not satisfied.)

If installation fails, then any new directories that were created will be removed. To override this behaviour, the option `keepDirectory` can be set to `true` using, for example, `InstallPackage("example" : keepDirectory)`, in which case such directories will be preserved for debugging.

Example

```
gap> InstallPackage("digraphs");
true
```

## 2.1.2 UpdatePackage

▷ `UpdatePackage(name[, interactive])` (function)

**Returns:** true or false

Attempts to update an installed package to the latest version. The first argument *name* should be a string specifying the name of a package installed in the user GAP root (for example, one installed using `InstallPackage` (2.1.1)), see (**Reference: GAP Root Directories**). The second argument *interactive* is optional, and should be a boolean specifying whether to confirm interactively before any directories are deleted (default value `true`).

If the package was installed via archive, the new version will be installed in a new directory, and the old version will be deleted. If installed via git, it will be updated using `git pull`, so long as there are no outstanding changes. If no newer version is available, no changes will be made.

This process will also attempt to fix the package if it is broken, for example if it needs to be recompiled or if one of its dependencies is missing or broken.

Returns `true` if a newer version was installed successfully, or if no newer version is available. Returns `false` otherwise.

Example

```
gap> UpdatePackage("io");
#I io version 4.6.0 will be installed, replacing 4.5.4
#I Saved archive to /tmp/tm7r5Ug7/io-4.6.0.tar.gz
Remove old version of io at /home/user/.gap/pkg/io-4.5.4 ? [y/N] y
true
```

## 2.1.3 RemovePackage

▷ `RemovePackage(name[, interactive])` (function)

**Returns:** true or false

Attempts to remove an installed package using its name. The first argument *name* should be a string specifying the name of a package installed in the user GAP root, see (**Reference: GAP Root Directories**). The second argument *interactive* is optional, and should be a boolean specifying whether to confirm certain decisions interactively (default value `true`).

Returns `true` if the removal was successful, and `false` otherwise.

Example

```
gap> RemovePackage("digraphs");
Really delete directory /home/user/.gap/pkg/digraphs-0.13.0 ? [y/N] y
true
```

## 2.1.4 InstallRequiredPackages

▷ `InstallRequiredPackages()` (function)

**Returns:** `true` or `false`

Attempts to download and install the latest versions of all packages required for **GAP** to run. Currently these packages are **GAPDoc**, **primgrp**, **SmallGrp**, and **transgrp**. Returns `false` if something went wrong, and `true` otherwise.

Clearly, since these packages are required for **GAP** to run, they must be loaded before this function can be executed. However, this function installs the packages in the `~/.gap/pkg` directory, so that they can be managed by **PackageManager** in the future, and are available for other **GAP** installations on the machine.

## 2.2 Info warnings

### 2.2.1 InfoPackageManager

▷ `InfoPackageManager` (info class)

Info class for the **PackageManager** package. Set this to the following levels for different levels of information:

- 0 - No messages
- 1 - Problems only: messages describing what went wrong, with no messages if an operation is successful
- 2 - Directories and versions: also displays informations about package versions and installation directories
- 3 - Progress: also shows step-by-step progress of operations
- 4 - All: includes extra information such as whether `curlInterface` is being used, and package info validation

Set this using, for example `SetInfoLevel(InfoPackageManager, 1)`. Default value is 3.

## 2.3 Manual compilation

### 2.3.1 CompilePackage

▷ `CompilePackage(name)` (function)

**Returns:** `true` or `false`

Attempts to compile an installed package. Takes one argument *name*, which should be a string specifying the name of a package installed in the user **GAP** root (for example, one installed using `InstallPackage` (2.1.1)), see (**Reference: GAP Root Directories**). Compilation is done automatically when a package is installed or updated, so in most cases this command is not needed. However, it may sometimes be necessary to recompile some packages if you update or move your **GAP** installation.

Compilation is done using the `etc/BuildPackages.sh` script bundled with `PackageManager`. If the specified package does not have a compiled component, this function should have no effect.

Returns `true` if compilation was successful or if no compilation was necessary. Returns `false` otherwise.

Example

```
gap> CompilePackage("orb");  
#I Running compilation script on /home/user/.gap/pkg/orb-4.8.3 ...  
true
```



# Index

`CompilePackage`, [7](#)

`InfoPackageManager`, [7](#)

`InstallPackage`, [5](#)

`InstallRequiredPackages`, [7](#)

`RemovePackage`, [6](#)

`UpdatePackage`, [6](#)