Google DeepMind



Highway: portable vector intrinsics

Jan Wassenberg
Software engineer

2024-09-19

Agenda

01 What, why, where, how

02 Porting code

03 Runtime dispatch

04 Design rationale

05 Users

Google Research

01

What, why, where, how



What is SIMD?

Single / same
Instruction / operation on
Multiple
Data (lanes)

16-32 fused multiply-add / cycle per core!



Google Research

Why SIMD?

"SIMD feels like magic!"
[Googler who saw a 10x speedup in a day's work]

- Widely available
  - x86, ARM, RISC-V, MIPS, ...
- Minimal incidental complexity
  - Same toolchain, memory space, debugger
  - No PCI-e latency
- Vendor-independent



Google Research

Where SIMD?

Anything involving kGCU and **arrays** of built-in types!

- Linear algebra (ML), image/video, audio samples
- Strings (strlen, JSON, CSV parsing, UTF validation)
- Hashing, Cryptography
- Database (bit packing, filter, join, vector search)
- QuickSelect (“Fast Top-K in ScaM”), QuickSort
- Computational biology
- Computer graphics



Google Research

Why Highway?

Same code, multiple platforms

Easy to port from existing intrinsics

Helps work around compiler bugs

Reliable and predictable performance

Also designed for variable vectors (SVE)



Google Research

Why not autovec?

OpenMP 4.0, armclang, Intel compiler

Minimal code changes, scalable

Brittle (maintenance, compiler upgrade)

Risk of poor codegen ("SIMD" memcpy)

```
movzx    ecx, byte [rax+rdi*4+8]
movd     xmm1, ecx
pinsrb   xmm1, [rax+rdi*4+0 ], 1
pinsrb   xmm1, [rax+rdi*4+12], 2
pinsrb   xmm1, [rax+rdi*4+4 ], 3
```



Google Research

Why not assembly?

Used in FFMPEG

Potentially more efficient

Error-prone: major penalty for

```
MOVAPS xmm0, xmm1 vs.
VMOVAPS xmm0, xmm1
```

Laborious (though macros help)

- Porting: FMLA vs. vfmadd132ps, ...
- Manual register allocation
- Beware ABI differences



Google Research

Why not intrinsics?

Widely used, also on MSVC

Error-prone

Compiler bugs (see next slide)

Laborious

- Porting: `_mm512_mask_mov_ps` vs. `_mm256_blendv_ps`

- Verbose:
```
_mm256_load_si256(
  reinterpret_cast<
    const __m256i*>(ptr))
```



Google Research

Compiler bugs

clang-6: incorrect codegen for partial vector writes. Workaround: memcpy instead of intrinsics
clang-6: incorrect ARMv7 codegen, read after write data hazard. Workaround: clobber memory
clang-6: suboptimal codegen for VBROADCASTI128. Workaround: inline assembly
clang-6: missing KORTEST for AVX-512. Workaround: treat masks as integers
clang-6: incorrect msan codegen. Abandoned: require clang-7

clang-7: unaligned spills in asan. User workaround: shorter variable lifetime

clang-8: various "Do not know how to split". Workaround: find op, replace with other
clang-8: inconsistent inlining/attribute requirements. Workaround: use pragma
clang-8: pragma must be at global scope. Workaround: HWY_BEFORE_NAMESPACE

clang-9: crash due to vector class constructor. Workaround: aggregate init

gcc 9.2: incorrect intrinsics for signed compare. Workaround: vector extension

Wasm: Workaround: emulate missing/broken instructions



Google Research

Highway library

https://github.com/google/highway

Example

Developed since 2017, open sourced 2019

Advice:

Connor Fitzgerald, Daniel Lemire
Jyrki Alakuijala, Povilas Kanapickas
Rich Winterton



Google Research

Under the hood

```
template <typename T>
HWY_API Vec256<T> IfVecThenElse(
     Vec256<T> mask, Vec256<T> yes, Vec256<T> no) {
#if HWY_TARGET <= HWY_AVX3
  const DFromV<decltype(yes)> d;
  const RebindToUnsigned<decltype(d)> du;
  using VU = VFromD<decltype(du)>;
  return BitCast(d, VU{_mm256_ternarylogic_epi64(
    BitCast(du, mask).raw, BitCast(du, yes).raw,
    BitCast(du, no).raw, 0xCA)});
#else
  return IfThenElse(MaskFromVec(mask), yes, no);
#endif
}
```



Google Research

Your code

```
void Squared(const float* in, float* out, size_t num) {
  ScalableTag<float> d; //  asks for full vector

  for (size_t i = 0; i < num; i += Lanes(d)) {
    const auto vec = LoadU(d, in + i);
    StoreU(Mul(vec, vec), d, out + i);
  }
  printf("F(x)->x^2, F(%.0f) = %.1f\n", in[2], out[2]);
}
```



Google Research

Example: RNG

```
class Xorshift128Plus {
 public:
  // 8 independent generators
  // (= single iteration for AVX-512)
  enum { N = 8 };

  HWY_INLINE HWY_MAYBE_UNUSED void
  Fill(uint64_t* HWY_RESTRICT random_bits) {
    // see next slide
  }

  // unsafe, requires class to be aligned
  HWY_ALIGN uint64_t s0_[N];
  HWY_ALIGN uint64_t s1_[N];
};
```

Google Research

Porting RNG

```
for (size_t i = 0; i < N; ++i) {
  auto s1 = s0_[i];
  const auto s0 = s1_[i];
  const auto bits = s1 + s0;
  s0_[i] = s0;
  s1 ^= s1 << 23;
  random_bits[i] = bits;
  s1 ^= s0 ^ (s1 >> 18) ^
        (s0 >> 5);
  s1_[i] = s1;
}
```

```
const ScalableTag<uint64_t> d;  // assume <= 512bit
for (size_t i = 0; i < N; i += Lanes(d)) {
  auto s1 = Load(d, s0_ + i);
  const auto s0 = Load(d, s1_ + i);
  const auto bits = s1 + s0;
  Store(s0, d, s0_ + i);
  s1 ^= ShiftLeft<23>(s1);
  Store(bits, d, random_bits + i);
  s1 ^= s0 ^ ShiftRight<18>(s1) ^
        ShiftRight<5>(s0);
  Store(s1, d, s1_ + i);
}
```

Google Research

02

Porting code



Annotate

AVX2: Clang/GCC require -mavx2 (unsafe) or function attribute

Could annotate each function with HWY_ATTR
Easy to forget, causes errors on other compilers

Or: single #pragma attribute/target (HWY_BEFORE_NAMESPACE)

- Convenient
- Compiler-specific
- Must be outside namespace (thanks Robert Obryk!)

```
HWY_BEFORE_NAMESPACE();
namespace myproject {
namespace HWY_NAMESPACE {
HWY_ATTR void MyFunc(float* HWY_RESTRICT out) {}
}  // namespace HWY_NAMESPACE
}  // namespace myproject
HWY_AFTER_NAMESPACE();
```

Google Research

Create vectors

```
// Defined by Highway:
template <typename Lane, size_t kLanes>
struct Simd {  // Empty tag type
  using T = Lane;
};
Type128 Zero(Simd<float, 4> /*tag*/);
Type256 Zero(Simd<float, 8> /*tag*/);


// Your code
const ScalableTag<float> d;  // = Simd<float, ??>
const auto zero = Zero(d);
const auto one = Set(d, 1.0f);
```

Google Research

Loops, memory

```
for (size_t x = 0; x < xsize;
-                            ++x) {
+                            x += Lanes(d)) {
-  const float xval = rowx[x];
-  const float yval = rowy[x];
+  const auto  xval = Load(d, rowx + x);
+  const auto  yval = Load(d, rowy + x);

-  const float scaler = s + (yw * (1.0f - s)) /
-                           (yw + yval * yval);
+  const auto  scaler = s + (yw * (one  - s)) /
+                       MulAdd(yval, yval, yw);

-  rownew[x] = scaler * xval;
+  Store(scaler * xval, d, rownew + x);
}
```

Google Research

Alignment

```
std::vector<float> rowx(128);
for (size_t x = 0; x < xsize; x += Lanes(d)) {
  // CRASH - unaligned
  const auto xval = Load(d, rowx.data() + x);
  // …
}

  // less efficient
  const auto xval = LoadU(d, rowx.data() + x);


// unsafe for member variables and large vectors
HWY_ALIGN float rowx[128];

// works for member variables and large vectors
hwy::AlignedFreeUniquePtr<float[]> rowx =
hwy::AllocateAligned<float>(128);
```

Google Research

Data layout

```
struct Point {
  float x;
  float y;
};
hwy::AlignedFreeUniquePtr<Point[]> points =
hwy::AllocateAligned<Point>(N);

const ScalableTag<float> d;

// mixes x and y in vector
auto mixed = Load(d, &points.data().x);

hwy::AlignedFreeUniquePtr<float[]> all_x_then_y =
hwy::AllocateAligned<float>(N * 2);
auto only_x = Load(d, all_x_then_y.data());
auto only_y = Load(d, all_x_then_y.data() + N);
```

Google Research

Branches

```
float RemoveRangeAroundZero(float w, float x) {
  return           x > w ? x - w :
                        x < -w ?    x + w : 0.0f;
}
template<class V>
V RemoveRangeAroundZero(V w, V x) {
  return IfThenElse(x > w, x - w,
         IfThenElseZero(x < Neg(w), x + w));
}

bool AllPositiveIntegers(int v) {
  return v >= 0;
}
template<class V>
bool AllPositiveIntegers(V v) {
  // avoids/hides 'zero'/'sign bit' constant
  return AllTrue(Abs(v) == v);
}
```

Google Research

[Headers]

```
// Special include guard
#if defined(MYPROJECT_FILE_INL_H_) == \
    defined(HWY_TARGET_TOGGLE)
#ifdef MYPROJECT_FILE_INL_H_
#undef MYPROJECT_FILE_INL_H_
#else
#define MYPROJECT_FILE_INL_H_
#endif

// header contents, like normal SIMD module

#endif  // include guard
```

"Toggles" include guard macro - prevents multiple inclusion within a particular target

Thanks to Lode Vandevenne for this clever idea!

Google Research

03

Runtime dispatch



Multi-target

```
// At top of file, before other hwy includes
#undef HWY_TARGET_INCLUDE
#define HWY_TARGET_INCLUDE "path/filename.cc"
#include <hwy/foreach_target.h>

HWY_BEFORE_NAMESPACE();
// implementation - compiled once per target
HWY_AFTER_NAMESPACE();

#if HWY_ONCE
namespace myproject {
HWY_EXPORT(MyFunc);  // defines function table

void Caller() {
  // dispatches to best available implementation
  HWY_DYNAMIC_DISPATCH(MyFunc)(args);
}
#endif
```

Google Research

Definitions

Target ≔ instruction set (e.g. AVX2)

Baseline ≔ what compiler targets (= CPU requirement)
Determined by -mavx2 or `HWY_BASELINE_TARGETS`

Enabled ≔ non-denylisted targets
Determined by known issues / `HWY_DISABLED_TARGETS`

Static target ≔ best enabled baseline

Attainable ≔ extra targets Highway can generate
Determined by compiler: all enabled on x86, or baseline

Superseded: baseline \ static target
If SSE4 baseline, skip scalar to reduce code size

[Dynamic] targets ≔ configurable: { scalar | static | attainable | attainable \ superseded }

Google Research

Dispatching

```
// Direct call into baseline from normal code:
// (Can make sense if baseline is sufficient -
// avoid generating for all targets)
HWY_STATIC_DISPATCH(MyFunc)(args);

SupportedTargets()  // bitfield, depends on CPU

// Indirect call into best available SIMD:
HWY_DYNAMIC_DISPATCH(MyFunc)(args);

// Call for each target from anywhere:
hwy::RunTest(func, args);
```

gTest adapters also provided.

Google Research

04

Design rationale



Simd<T, N>:: ?

SVE backend: as of 2021-05, vectors are sizeless types

Cannot be a class member

➡️API based on overloaded functions

Can we have Load(V(), ptr)?

No, V is builtin on SVE, cannot indicate limit on #lanes

What about Load(V(), IntConst<N>, ptr)?

Error-prone - can break if not all call sites updated

➡️still have tag argument called Simd<T, N>

Google Research

Why auto?

Rarely need to know vector type, can deduce

Even for output params: `auto out = Undefined(d);`

Large number of vector types (50-70)

Types: {u, i} x {8, 16, 32, 64} , f32, f64

Lanes: 1, 2, 4, 8, 16, 32, 64

For portability, encourage size-agnostic code

But: auto everywhere hard to read / understand

➡️compromise: user-defined typedef:

`using V = decltype(Zero(d));` or

`using V = Vec<decltype(d)>;`

Google Research

Why not stack?

SVE: max size 256 bytes. Wasteful on stack

RISC-V V: large upper bound: 64K elements
One implementation actually has 16 KiB vectors.

➡️use hwy/aligned_allocator.h and actual size: `Lanes(d)`

Google Research

Why >1 header?

Including everything actually expensive (huge immintrin.h)

base.h for users / headers who just want
HWY_RESTRICT (function parameter) or
HWY_REP4 (define input for LoadDup128) etc.

targets.h useful for callers who want to know/influence
which target is active

highway.h only for implementers of SIMD modules, not their users

05

Users



Highway ecosystem

4.1K Github stars
41 contributors with >1 CL
>100 unique Git cloners per day

Available in dozens of package managers

Evaluation of C++ SIMD Libraries:
"Highway excelled with a strong performance across multiple SIMD extensions [..]. Thus, Highway may currently be the most suitable SIMD library for many software projects."



Google Research

JPEG XL

Next-generation image compression. jpeg.org/jpegxl

Uses integer (random generation) and floating-point:

- DCT, filtering, color conversion, noise synthesis
- Quantization, function approximations, ...

Runtime dispatch, 1.4x speedup from AVX2 to AVX-512

Main dev team: 9 engineers, positive feedback on Highway API

Shipping on iOS 17 and OS X 14



Google Research

Gemma.cpp

Lightweight, standalone C++ LLM inference on github

Supports Gemma, RecurrentGemma, PaliGemma (soon)

8-bit floating-point decompression, bf16 arithmetic

Faster than llama.cpp on SKX/Zen4 CPUs

Experimentation platform for inference R&D



Google Research

Also related

VQSort: fastest known QuickSort
- Vectorized partitioning and *2D* sorting network

HighwayHash: fast MAC/pseudorandom function
- Built around SIMD multiply and permute
- 64, 128, 256 bit result (1024 bit internal state)
- Difficult to create collisions (> 2^{64} work)
- Similar SIMD via intrinsics + runtime dispatch

Randen: Abseil's random generator
- Cryptographic (indistinguishable from random)
- Faster than some common insecure generators
- Enabled by SIMD AES (x86, ARM, POWER)
- Simpler SIMD wrapper over intrinsics





Google Research

Questions/contact

janwas@google.com highway-users@google.com
Staff Software Engineer

More info: go/hwy, workshop slides

Google Research